

SPC Selected Products GmbH · D-42289 Wuppertal · Brucknerweg 26
Fon: +49 202 - 57494764 · Fax: +49 202 - 87088403 · info@spc-selectedproducts.de

Technical Information: SPC Corrosion Protection Fluid



Chemical name :	SPC Corrosion Protection Fluid
	Water Repellent and Corrosion Protection for Ferrous and Non-Ferrous Metals
Packing :	drums / IBC / bulk
Synonym :	Korrosionsschutzmittel, Wasserverdrängungsfluid, Schutzbeschichtung für Metalle

General informations :

SPC Corrosion Protection Fluid is a high-quality water-displacing and anti-corrosion agent specially developed for the protection of ferrous and non-ferrous metals.

It forms a dry, wax-like film that does not gum up and is easy to wash off.

SPC Corrosion Protection Fluid offers excellent water-displacing properties and prevents the formation of condensation under the protective film. When stored indoors, it effectively protects metals against corrosion for up to 24 months. For medium-term outdoor storage, the application of two coats is recommended. SPC Corrosion Protection Fluid is barium-free and can be filled into customer-specific containers or offered as a white label product.

We also offer SPC Corrosion Protection Fluid as a white label product for resellers or fill it into customer-specific containers.

Application :

The SPC corrosion protection fluid can be applied by brushing, spraying, or dipping. For optimal protection, the surface should be clean and dry. For outdoor storage, it is recommended to apply two coats. The drying time is approximately 30 minutes at room temperature (20 °C).

Hazard Informations :

SPC corrosion protection fluid is subject to labeling requirements under the Hazardous Substances Ordinance and EC directives. Always read the label and product information before use. Always store the product in a dark, cool, and dry place and keep the container tightly closed.

Version: 30.07.2026

This data is only for your information purposes and does not imply a guarantee for a certain application.